

TECHNICAL DATA SHEET

STRIPP IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

83x249 mm


Material : CALCYT® plaster



REMOTE LED DRIVER ON/OFF

REF N° 697 00 006 8W

REF N° 697 00 015 15W

REF N° 697 00 025 25W

230V/50Hz -  - current controlled

 -  - IP20 - 350mA - not dimmable

STRIPP LED DIM 100 LM







REF N° 144 60 501 CRI 80 warm white 2200°K

REF N° 144 60 001 CRI 90 warm white 2700°K

REF N° 144 60 101 CRI 90 warm white 3000°K

REF N° 144 60 201 CRI 90 neutral white 4000°K

REF N° 144 60 301 royal blue

 - 1W - excl. LED driver - current controlled 350 mA -  -  -  -  -  - serial wiring - 3 Step MacAdam
Requires remote LED driver - 350 mA

REMOTE LED DRIVER DIM

REF N° 697 60 006 6W 1-10V

REF N° 697 60 015 15W 1-10V


REF N° 697 30 015 15W DALI

REF N° 697 60 025 25W 1-10V DALI PUSH

REF N° 697 60 040 40W 1-10V DALI PUSH

REF N° 697 70 009 9W PHASE DIM (tr. edge)

REF N° 697 70 017 17W PHASE DIM

230V/50Hz -  - current controlled

 -  - IP20 - 350mA - dimmable

STRIPP LED DIM 200 LM







REF N° 144 62 501 CRI 80 warm white 2200°K

REF N° 144 62 001 CRI 90 warm white 2700°K

REF N° 144 62 101 CRI 90 warm white 3000°K

REF N° 144 62 201 CRI 90 neutral white 4000°K

REF N° 144 62 301 royal blue

 - 2W - excl. LED driver - current controlled 350 mA -  -  -  -  -  - serial wiring - 3 Step MacAdam
Requires remote LED driver - 350 mA

STRIPP LED DIM 400 LM







REF N° 144 61 501 CRI 80 warm white 2200°K



REF N° 144 61 001 CRI 90 warm white 2700°K

REF N° 144 61 101 CRI 90 warm white 3000°K

REF N° 144 61 201 CRI 90 neutral white 4000°K

REF N° 144 61 301 royal blue

 - 4W - excl. LED driver - current controlled 350 mA -  -  -  -  -  - serial wiring - 3 Step MacAdam
Requires remote LED driver - 350 mA



Ready for installation in solid walls
Optional plasterkit for installation into gypsum walls

PLASTERKIT STRIPP

REF N° 744 01 000 For mounting into gypsum walls

Housing: perforated aluminium

