

PHOTOMETRIC TEST REPORT

MINIMA PRO SQUARE FIXED IP65
- MATT WHITE - 4001091

astro

MINIMA PRO SQUARE FIXED IP65 - MATT

astro

LIGHT EFFICIENCY:

110 Lumen/Watt

LIGHT QUALITY:

CRI: 95.5

COLOR TEMPERATURE:


3022 K

OUTPUT: 1297 lm

PEAK: 2274 cd

POWER: 11.8 W

PF: 0.95



Tracking number: [n/a](#)

Product name:

Minima Pro Square Fixed IP65 - Matt
White - 4001091

Item number:


MSF-MW-HE30G1-50G1-X-D1

Date and time:

03/02/2025 13:50:14

Description:

IP65 LED Downlight




46.7°




CIE 1931
x: 0.438
y: 0.409



SPECTRA



POWER




COLOR DETAILS




CIE 1931 ZOOM

TM30: 93.1



CRI: 95.5 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97.0	97.0	96.2	97.7	96.5	97.5	94.5	87.6	68.5	91.7	97.3	86.7	96.5	96.5	92.6


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92.3	95.3	93.1	96.8	94.5	94.7	95.7	96.9	97.0	94.7	93.4	88.4	86.6	86.8	89.9	86.4

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
88.0	93.2	92.4	94.3	95.3	93.9	94.8	96.7	98.0	96.1	95.4	95.8	96.3	90.5	88.9

CQS: 93.2









COLOR PARAMETERS

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3022 K	95.5	68.5	93.1	100.0	93.2	0.438	0.409	0.249	0.349	0.0017


Rf 93.1
Fidelity index Rf

Rg 100.0
Gammut index Rg

Hue Bin	Rf	Graphic shifts (%)	
		Chroma	Hue
1	92	-4%	-1%
2	95	-2%	1%
3	93	-1%	3%
4	97	0%	1%
5	94	-1%	3%
6	95	2%	2%
7	96	0%	-1%
8	97	2%	0%
9	97	0%	1%
10	95	-1%	2%
11	93	1%	5%
12	88	5%	-3%
13	87	3%	-10%
14	87	3%	-10%
15	90	-1%	-6%
16	86	-3%	-10%



BEAM DETAILS



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2274lx	569lx	253lx	142lx	91lx	63lx	46lx	36lx	28lx	23lx	19lx	16lx	13lx	12lx	10lx	9lx	8lx	7lx	6lx	6lx
211.3fcd	52.8fcd	23.5fcd	13.2fcd	8.5fcd	5.9fcd	4.3fcd	3.3fcd	2.6fcd	2.1fcd	1.7fcd	1.5fcd	1.3fcd	1.1fcd	0.9fcd	0.8fcd	0.7fcd	0.7fcd	0.6fcd	0.5fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2274	2269	2258	2233	2189	2126	2039	1930	1800	1646	1471	1277	1070	859	655	475	328	214	133	77
100%	100%	99%	98%	96%	93%	90%	85%	79%	72%	65%	56%	47%	38%	29%	21%	14%	9%	6%	3%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2274	2269	2258	2233	2189	2126	2039	1930	1800	1646	1471	1277	1070	859	655	475	328	214	133	77
100%	100%	99%	98%	96%	93%	90%	85%	79%	72%	65%	56%	47%	38%	29%	21%	14%	9%	6%	3%

Intensities in 180° c-plane


0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2274	2269	2258	2233	2189	2126	2039	1930	1800	1646	1471	1277	1070	859	655	475	328	214	133	77
100%	100%	99%	98%	96%	93%	90%	85%	79%	72%	65%	56%	47%	38%	29%	21%	14%	9%	6%	3%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2274	2269	2258	2233	2189	2126	2039	1930	1800	1646	1471	1277	1070	859	655	475	328	214	133	77
100%	100%	99%	98%	96%	93%	90%	85%	79%	72%	65%	56%	47%	38%	29%	21%	14%	9%	6%	3%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
46.7°	67.5°	78.1°	99.7%	99.1%


ISO CANDELA DIAGRAM



10%	227 cd
20%	455 cd
30%	682 cd
40%	910 cd
50%	1137 cd
60%	1364 cd
70%	1592 cd
80%	1819 cd
90%	2047 cd

Conditions:
Number of c-planes: 8
Candela at center: 2274 cd

ISO LUX DIAGRAM



3%	0.682 lx
5%	1.14 lx
10%	2.27 lx
30%	6.82 lx
50%	{LUX_10M50} lx

Conditions:
Number of c-planes: 8
Lux at center: 22.7 lx

Lux distribution on a surface
when lamp is mounted at 10
meters from the surface.

UGR

GLARE EVALUATION ACCORDING TO UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18.7	19.2	18.8	19.4	19.6	18.7	19.2	18.8	19.4	19.6
	3H	18.4	19.1	18.8	19.3	19.4	18.4	19.1	18.8	19.3	19.4
	4H	18.3	19.0	18.7	19.2	19.4	18.3	19.0	18.7	19.2	19.4
	6H	18.3	18.8	18.6	19.1	19.5	18.3	18.8	18.6	19.1	19.5
	8H	18.3	18.8	18.6	19.1	19.5	18.3	18.8	18.6	19.1	19.5
	12H	18.2	18.7	18.6	19.1	19.5	18.2	18.7	18.6	19.1	19.5
4H	2H	18.3	19.0	18.7	19.2	19.4	18.3	19.0	18.7	19.2	19.4
	3H	18.2	18.7	18.6	19.1	19.5	18.2	18.7	18.6	19.1	19.5
	4H	18.1	18.5	18.5	19.0	19.5	18.1	18.5	18.5	19.0	19.5
	6H	18.0	18.5	18.5	18.8	19.2	18.0	18.5	18.5	18.8	19.2
	8H	17.9	18.4	18.4	18.7	19.1	17.9	18.4	18.4	18.7	19.1
	12H	17.9	18.2	18.4	18.6	19.1	17.9	18.2	18.4	18.6	19.1
8H	4H	17.9	18.4	18.4	18.7	19.1	17.9	18.4	18.4	18.7	19.1
	6H	17.9	18.2	18.4	18.6	19.2	17.9	18.2	18.4	18.6	19.2
	8H	17.9	18.1	18.4	18.6	19.2	17.9	18.1	18.4	18.6	19.2
	12H	17.8	18.0	18.4	18.5	19.1	17.8	18.0	18.4	18.5	19.1
12H	4H	17.9	18.2	18.4	18.6	19.1	17.9	18.2	18.4	18.6	19.1
	6H	17.9	18.1	18.4	18.6	19.2	17.9	18.1	18.4	18.6	19.2
	8H	17.8	18.0	18.4	18.5	19.1	17.8	18.0	18.4	18.5	19.1
Variation of the observer position for the luminaire distance S											
S = 1.0H		6.4 / -13.3					6.4 / -13.3				
S = 1.5H		9.2 / -15.6					9.2 / -15.6				
S = 2.0H		11.2 / -17.2					11.2 / -17.2				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 1297 lm total luminous flux											

COEFFICIENTS OF UTILIZATION

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	99	98	97	97	95
2	110	105	102	99	107	104	100	98	100	98	96	97	95	93	95	93	92	90
3	105	99	95	92	103	98	94	91	96	92	90	93	90	88	91	89	87	85
4	101	94	89	86	99	93	89	85	91	87	84	89	86	83	87	85	82	81
5	97	89	84	81	95	89	84	80	87	83	80	85	82	79	84	81	78	77
6	93	85	80	76	91	84	80	76	83	79	76	82	78	75	80	77	75	73
7	89	81	76	72	88	80	76	72	79	75	72	78	74	71	77	74	71	70
8	86	77	72	69	84	77	72	69	76	71	68	75	71	68	74	70	68	67
9	82	74	69	65	81	74	69	65	73	68	65	72	68	65	71	67	65	64
10	79	71	66	63	78	70	66	62	70	65	62	69	65	62	68	65	62	61

LAMPS (number of lamps)

LUMINAIRE BUDGETARY DIAGRAM



ZONAL LUMEN SUMMARY

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
211 lm	512 lm	433 lm	121 lm	12.0 lm	3.99 lm	1.24 lm	0.405 lm	0.154 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.096 lm	0.089 lm	0.115 lm	0.183 lm	0.360 lm	0.583 lm	0.633 lm	0.420 lm	0.126 lm

FLICKER

FLICKER CURVE (COMPLETE SAMPLED)



FLICKER FRAME (FRAME OF ONE FLICKER)



FLICKER FFT (FREQUENCY SCOPE OF FLICKER)



FLICKER RESULTS:

Flicker frequency:	n/a Hz
Flicker index:	n/a
Flicker percentage:	n/a %
SVM: (Visual flicker)	n/a

FLICKER CONDITIONS:

Sample rate:	n/a samples/second
--------------	--------------------