
THREE-CIRCUIT TRACK WALL WASHER

Blit Track


FARO
Three-circuit track system





210 mm · dimensions in mm





300 mm · dimensions in mm

A minimalist wall washer in aluminium and glass, in 210 mm and 300 mm lengths. Its asymmetric optic throws a soft, even wash of light across walls, shelving and displays, and pairs naturally with spotlights and linear lights on the same track.

SPECIFICATIONS

Mounting	Faro three-circuit (3-phase) track
Voltage	220–240 V, 50/60 Hz
Power	20 W (210 mm) or 33 W (300 mm)
Light source	LED, driver included
Luminous flux	1633–3623 lm (see table)
CRI	90
Colour temperature	2700 K, 3000 K or 4000 K
Colour consistency	MacAdam 3 step
Optic	Asymmetric wall wash
Adjustment	Rotates 355°, tilts 30°
Rated life	50,000 h (L90/B10)
Protection	IP20, for indoor use
Materials	Aluminium and glass
Finish	Matt white or matt black
Control	On/Off or DALI
Size	210 or 300 mm wide, 185 mm overall height, 40 mm deep

LIGHT OUTPUT (CRI 90)

	210 mm, 20 W	300 mm, 33 W
2700 K	1,633 lm	3,412 lm
3000 K	1,684 lm	3,517 lm
4000 K	1,734 lm	3,623 lm

Luminous flux from Faro's catalogue.

CONTROL

On/Off	Switched, not dimmable
DALI	Needs Faro DALI track and connectors

Each light's adapter selects one of the track's three circuits.

ORDERING CODES

Blit Track

FARO
24 variants

Every variant, grouped by control and finish. Codes are our stock codes (Faro reference with an FA prefix).

Code	Model	Colour	Output
On/Off · Matt Black			
FA012792792	210 mm	2700K	1,633 lm
FA012793092	210 mm	3000K	1,684 lm
FA012794092	210 mm	4000K	1,734 lm
FA012892792	300 mm	2700K	3,412 lm
FA012893092	300 mm	3000K	3,517 lm
FA012894092	300 mm	4000K	3,623 lm
On/Off · Matt White			
FA012792791	210 mm	2700K	1,633 lm
FA012793091	210 mm	3000K	1,684 lm
FA012794091	210 mm	4000K	1,734 lm
FA012892791	300 mm	2700K	3,412 lm
FA012893091	300 mm	3000K	3,517 lm
FA012894091	300 mm	4000K	3,623 lm
DALI · Matt Black			
FA012792792D	210 mm	2700K	1,633 lm
FA012793092D	210 mm	3000K	1,684 lm
FA012794092D	210 mm	4000K	1,734 lm
FA012892792D	300 mm	2700K	3,412 lm
FA012893092D	300 mm	3000K	3,517 lm
FA012894092D	300 mm	4000K	3,623 lm
DALI · Matt White			
FA012792791D	210 mm	2700K	1,633 lm
FA012793091D	210 mm	3000K	1,684 lm
FA012794091D	210 mm	4000K	1,734 lm
FA012892791D	300 mm	2700K	3,412 lm
FA012893091D	300 mm	3000K	3,517 lm
FA012894091D	300 mm	4000K	3,623 lm