

DATA SHEET

SFERE 28 | 350 mA

1:1



Art. no.	Luminaire type	lm	mA	Watt
2785__	SFERE 28 Semi-recessed spotlight rotatable/tiltable 240°/70° for installation in SYSTEM DOT 28 solid aluminium incl. bayonet	400	350	4

Specification **Tender specification**


Compact semi-recessed spotlight of spherical design with shallow installation depth (ET) of 50 mm; part of a system that essentially enables flexible lighting solutions through the interaction of luminaire modules and recessed modules; tool-free, fast mounting and maintenance via bayonet lock, with luminaire accessories (recessed modules) selected separately according to ceiling system and design requirements; luminaire body machined from solid aluminium and anodised or coated; bayonet in black plastic with a velvet-matt finish; holder integrated flush with the ceiling; swivel arm in painted stainless steel; luminaire rotatable 240° and tiltable 70°; light distribution direct downlight; aluminium-vapour-coated and UV-protective-lacquered plastic reflector; precise light distribution with very good glare control; light-exit diameter only 14 mm; operating mode: constant current 350 mA; external control gear available separately; LED module power consumption: 4 W; dimensions: Ø 38 mm, H 66 mm (luminaire with swivel arm); installation depth (ET): min. 50 mm; colour rendering: typ. RA 93; luminaire luminous flux: 400 lm; colour tolerance (McAdam/SDCM): 3; LED lifetime: L80/B50 > 55,000 h; energy efficiency class: A+; degree of protection IP 20;

Anodised colours: snow silver, rose, gold, nutmeg bronze, cashmere gold, deep black

Coating colour: polar white RAL 9016

Beam angle FWHM: 25°/35°/55°

Light colour: 2700 K, 3000 K, 4000 K



GEORG BECHTER LICHT | SFERE 28 | Art. no. 2785__ or equivalent