

TECHNICAL DATA SHEET

200CENT GENERATION 2 TRIMLESS IP54

BATHROOM



Fixed (not adjustable) 0°

Cut out 114x134 mm

Recessed Depth - 95 mm

Material: CALCYT®
plaster

Reflector Finish : White

200 Cent 250 lm

LED 250 LM - 2,9 W - 2 step MacAdam Luminaire
delivered lumens : 192 LM - CRI 92 - R9 = 72 - Rf = 93 -
Rg = 100,5 - Requires remote LED driver - 700mA
Automatic polarity correction

Beam Angle	2700k	3000k
12°	BR250127921	BR250127821
18°	BR250127931	BR250127831
32°	BR250127941	BR250127841

200 Cent 500lm

LED 500 LM - 4,7 W - 2 step MacAdam Luminaire
delivered lumens : 378 LM- CRI 95 - R9 = 95 - Rf = 90 - Rg
= 104. - Requires remote LED driver - 700mA Automatic
polarity correction

Beam Angle	2700k	3000k
18°	BR253328921	BR253328821
24°	BR253328931	BR253328831
32°	BR253328941	BR253328841
44°	BR253328951	BR253328851

200 Cent 750lm

LED 750 LM - 7,4 W - 2 step MacAdam Luminaire
delivered lumens : 540 LM - CRI 92 - R9 = 72 - Rf = 93 -
Rg = 100,5 - Requires remote LED driver - 700mA
Automatic polarity correction

Beam Angle	2700k	3000k
28°	BR250129931	BR250129831
32°	BR250129941	BR250129841
38°	BR250129951	BR250129851

200 Cent 1000lm

LED 1000 LM - 8,9 W - 2 step MacAdam Luminaire
delivered lumens : 760 LM - F CRI 91 - R9 = 66 - Rf = 90 -
Rg = 101,5 - Requires remote LED driver - 700mA
Automatic polarity correction

Beam Angle	2700k	3000k
32°	BR250126931	BR250126831
36°	BR250126941	BR250126841
42°	BR250126951	BR250126851

INSTALLATION KIT

STANDARD (included)
installation system for ceiling 9 -12 -15 mm

BR200 99 025
installation system for gypsum ceiling 25 mm

BR20099030
installation system for gypsum ceiling 30 mm

OPTIONAL COLOURS ON REQUEST



Black




Sand



Silver Bronze



Bronze



Brass

