




# Gradiminiparete led retinato



22 cm  
8<sup>5/8</sup>"



25,5 cm  
6"




26 cm  
6<sup>3/4</sup>"



luminaire	
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	wall
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE  (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025


light source	
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	



## versions



**Gradiminiparete led retinato**  
chrome  
cod 516L



**Gradiminiparete led retinato**  
satin nickel-plated  
cod 586L



**Gradiminiparete led opalescente**  
chrome  
cod 527L



**Gradiminiparete led opalescente**  
satin nickel-plated  
cod 587L




**Gradiminiparete led tuttopallescente**  
chrome  
cod 581L




**Gradiminiparete led tuttopallescente**  
satin nickel-plated  
cod 588L

# Gradiminiparete led opalescente



22 cm  
8<sup>5/8</sup>"




25,5 cm  
6"

26 cm  
6<sup>2/4</sup>"




luminaire	
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	wall
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE  (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025


light source	
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	



## versions



**Gradiminiparete led retinato chrome**  
cod 516L



**Gradiminiparete led retinato satin nickel-plated**  
cod 586L



**Gradiminiparete led opalescente chrome**  
cod 527L



**Gradiminiparete led opalescente satin nickel-plated**  
cod 587L




**Gradiminiparete led tuttopallescete chrome**  
cod 581L




**Gradiminiparete led tuttopallescete satin nickel-plated**  
cod 588L

# Gradiminiparete led

## tuttopalescente




22 cm  
8<sup>5/8</sup>"





25,5 cm  
6"

26 cm  
6<sup>2/4</sup>"




	luminaire
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	wall
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE  (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025


	light source
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	




### versions




**Gradiminiparete led** retinato  
chrome  
cod 516L



**Gradiminiparete led** retinato  
satin nickel-plated  
cod 586L



**Gradiminiparete led** opalescente  
chrome  
cod 527L



**Gradiminiparete led** opalescente  
satin nickel-plated  
cod 587L



**Gradiminiparete led** tuttopalescente  
chrome  
cod 581L



**Gradiminiparete led** tuttopalescente  
satin nickel-plated  
cod 588L