





Reflector silver Reflector black



1 - 25mm

78 mm, ET 106 mm



Downlight aus Aluminium
Schwarz oder weiß pulverbeschichtet
Perfekte entblendung durch schwarzen
Kunststoff hochglanz Reflektor schwarz oder silber
Konverter separat ordern

Recessed downlight in aluminium
Black or white powder-coated
Perfect anti-glare due to black or silver high-gloss grid
Please order converter separately

Downlight in alluminio, Verniciato a polvere in nero
Verniciato a polvere in nero o bianco
Anti-abbagliamento garantito da una griglia nera lucida
Converter da ordinare separatamente

Downlight encastré en aluminium, laquée noir
Laquée noir ou blanc
Grille basse-luminance
convertiseur à commander séparément

UGR <16

LED 3500K auf Anfrage / on request

Universal-Betoneinbauehäuse: siehe Seite 498-499
Universal concrete housing: see page 498-499

A++ - A

IP20

DARK NIGHT SMALL R

Binning SDCM 3 exkl. Konverter / excl. converter

Power feed

350mA - 13W

500mA - 19W

Order converter not dimm.
Order converter Dali dimm.

24-127530
24-123403

24-127532
24-123403

684-0010205WWXX
684-0010305WWXX

COLOUR
REFLECTOR

	lm	lm	lm	lm	lm	lm
silver	1070	1110	1190	1430	1490	1600
black	1070	1110	1190	1430	1490	1600

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

WW = LICHTFARBE/LIGHT COLOUR

XX = FARBE / COLOUR

	LED 2700K = 43	PREMIUM CRI >90
	LED 3000K = 49	PREMIUM CRI >90
	LED 4000K = 24	CRI >90

	silver = 05
	black = 06

LED CONVERTER DARK NIGHT S

24-127530
24-127532
24-123403

schaltbar/switchable
schaltbar/switchable
DALI dimm.

for 350mA
for 500mA
for 350 - 500mA

L 130 x B 42 x H 30mm
L 130 x B 42 x H 30mm
L 111 x B 52 x H 22mm

