



## LOG OUT UP/DOWN W

220-240V AC/DC · CRI >80 · Binning SDCM 3

### SYS 2 x 21W

**mp:** 3000K = 3500lm / 4000K = 3690lm  
**pm:** 3000K = 3720lm / 4000K = 3920lm

**581-409X..** L: 870mm  
**581-4010X..** L: 870mm

### SYS 2 x 27W

**mp:** 3000K = 4670lm / 4000K = 4930lm  
**pm:** 3000K = 4970lm / 4000K = 5230lm

**581-419X..** L: 1156mm  
**581-4110X..** L: 1156mm

### SYS 2 x 34W

**mp:** 3000K = 5840lm / 4000K = 6160lm  
**pm:** 3000K = 6210lm / 4000K = 6540lm

**581-429X..** L: 1441mm  
**581-4210X..** L: 1441mm

### SYS 2 x 54W

**mp:** 3000K = 9350lm / 4000K = 9860lm  
**pm:** 3000K = 9940lm / 4000K = 10470lm

**581-439X..** L: 2299mm  
**581-4310X..** L: 2299mm

LED Wandleuchte aus stranggepresstem Aluminiumprofil  
 Oberfläche eloxiert, weiß oder schwarz pulverbeschichtet  
 Abdeckung mit Mikroprismenoptik oder Opaldiffusor  
 Abstrahlung mit Direkt- und Indirektanteil  
 Inkl. Wandbefestigungen

LED wall profile made of extruded aluminium  
 Anodised surface, black or white powder coated  
 Opal or microprismatic diffuser  
 Up and downlight emission  
 Wall fixation included

Profilo da parete a LED in alluminio estruso  
 Anodizzato o verniciato a polveri in bianco o nero  
 Diffusore opale o microprismatico  
 Emissione diretta ed indiretta  
 Compreso di fissaggio a parete

Profil de paroi à LED en aluminium extrudé  
 Anodisé ou vernissé à poudres en blanc ou noir  
 Diffuseur opal ou en microprisme  
 Émission directe et indirecte  
 Complet de fixation à paroi

Dimmbare Versionen / dimmable versions  
**581-XXXXad** = analog dimm. 1 - 10 V  
**581-XXXXddd** = DALI dimm.

= LED 3000K  
 = LED 4000K

= UGR<19

-

IP20

### SYS 2 x 68W

**mp:** 3000K = 11690lm / 4000K = 12320lm  
**pm:** 3000K = 12420lm / 4000K = 13090lm

**581-449X..** L: 2869mm  
**581-4410X..** L: 2869mm

### SYS 2 x 81W

**mp:** 3000K = 14030lm / 4000K = 14790lm  
**pm:** 3000K = 14910lm / 4000K = 15710lm

**581-459X..** L: 3442mm  
**581-4510X..** L: 3442mm

### SYS 2 x 101W

**mp:** 3000K = 17540lm / 4000K = 18480lm  
**pm:** 3000K = 18640lm / 4000K = 19640lm

**581-469X..** L: 4297mm  
**581-4610X..** L: 4297mm

## ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

**X** = FARBE / COLOUR

white = 5  
 black = 6  
 aluminium anodized = 8

**..** = ABDECKUNG / COVER

microprismatic = **mp**

PMMA opal = **pm**

