



LED Einbauspot aus Aluminium
Oberfläche in perlchrom oder chrom
Facettierte Linse 30°
Zubehör separat ordern (S. 528)
Geeignet für den Außenbereich (IP 54)

LED recessed spotlight in aluminium
Pearl chrome or chrome surface
30° faceted lens
Order accessories separately (p. 528)
Outdoor suitable (IP54)

Incasso a LED in alluminio
Superficie in cromo satinato o cromo
Lente sfaccettata da 30°
Ordinare gli accessori separatamente (p. 528)
Per esterni (IP54)

Encastré à LED en aluminium
Superficie en chrome satiné ou chrome
Lentille à facettes de 30°
Commander les accessoires séparément (p. 528)
Pour extérieur (IP54)

W3 = LED 3000K

LED 2700K auf Anfrage / on request

A++ - **A**

IP 54


RADO WR

CRI>90
exkl. LED Konverter (separat ordern)
excl. LED converter (order separately)

SYS 2W · 500mA

56-6110ng2 126lm
56-6010ng2 126lm

56-6111ng2 126lm
56-6011ng2 126lm




MITO WR

CRI>90
exkl. LED Konverter (separat ordern)
excl. LED converter (order separately)

SYS 2W · 500mA

56-6118ng2 126lm
56-6018ng2 126lm

56-6119ng2 126lm
56-6019ng2 126lm



LED CONVERTER RADO/MITO

| | | | | |
|------------------|-------------|----------------------|-----------|-----------------------|
| 75-mp15 | 4W | schaltbar/switchable | for 500mA | L 51 x B 32 x H 18mm |
| 24-122428 | 6W | 1 - 10V / PUSH Dimm. | for 500mA | L 67 x B 50 x H 22mm |
| 24-122201 | 20W* | schaltbar/switchable | for 500mA | L 111 x B 52 x H 22mm |
| 24-123400 | 20W* | 1 - 10V / PUSH Dimm. | for 500mA | L 111 x B 52 x H 22mm |
| 24-151403 | 20W* | DALI Dimm. | for 500mA | L 111 x B 52 x H 22mm |

* nicht für den Einbau in Unterputzdose Ø68 geeignet
* not suitable for mounting in housing Ø68

