

## RIDE LENS R

CRI >90 · Binning SDCM 3

exkl. LED Konverter (separat ordern) / excl. LED converter (order separately)

### LED 6W · 500mA


634-002040123XX	W2	15°	460lm
634-002040129XX	W3	15°	510lm
634-002040124XX	W4	15°	550lm

634-002040623XX	W2	34° + 15°	440lm
634-002040629XX	W3	34° + 15°	480lm
634-002040624XX	W4	34° + 15°	520lm

634-002040323XX	W2	45°	460lm
634-002040329XX	W3	45°	510lm
634-002040324XX	W4	45°	550lm

37mm x L 111mm, ET: 80mm

7 - 40 mm



### LED KONVERTER / LED CONVERTER

<b>24-122201</b>	500mA, not dimmable	1-2 RIDE 6W
<b>24-123403</b>	500mA, DALI dimm.	1-2 RIDE 6W



Schmale LED Einbauleuchte

Oberfläche eloxiert, weiß oder schwarz pulverbeschichtet  
Zurückversetzte Linsen mit verschiedenen Abstrahlwinkeln  
Perfekte Entblendung durch schwarzen Hochglanzraster

Slim LED recessed luminaire

Anodised surface, black or white powder-coated  
Recessed lense with different beam angles  
Perfect anti-glare due to black high-gloss grid

Incasso LED a ridotto ingombro

Finitura anodizzata, verniciatura a polveri bianca o nero  
Lente retrocessa con differenti fasci di emissione  
Griglia nera lucida per controllo anti-abbagliamento

Encastré fin à LED

Anodisé ou vernissé à poudres en blanc ou noir  
Optique placée en fond combinée avec darklight  
Contrôle anti-éblouissement optique darklight

UGR <19

W2 = LED 2700K

W3 = LED 3000K

W4 = LED 4000K

A++ - A

IP20 CE

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

XX = FARBE/COLOUR

W white = 05

S black = 06

AE aluminium anodized = 08

### LED 17W · 500mA

634-002010123XX	W2	15°	1400lm
634-002010129XX	W3	15°	1530lm
634-002010124XX	W4	15°	1650lm

634-002010623XX	W2	34° + 15°	1330lm
634-002010629XX	W3	34° + 15°	1450lm
634-002010624XX	W4	34° + 15°	1560lm

634-002010323XX	W2	45°	1400lm
634-002010329XX	W3	45°	1530lm
634-002010324XX	W4	45°	1650lm

37mm x L 301mm, ET: 80mm

7 - 40 mm



### LED KONVERTER / LED CONVERTER

<b>24-122201</b>	500mA, not dimmable	1 RIDE 17W
<b>24-123403</b>	500mA, DALI dimm.	1 RIDE 17W

### LED 31W · 900mA


634-002020123XX	W2	15°	2560lm
634-002020129XX	W3	15°	2780lm
634-002020124XX	W4	15°	3000lm

634-002020623XX	W2	34° + 15°	2420lm
634-002020629XX	W3	34° + 15°	2630lm
634-002020624XX	W4	34° + 15°	2840lm

634-002020323XX	W2	45°	2560lm
634-002020329XX	W3	45°	2780lm
634-002020324XX	W4	45°	3000lm

37mm x L 588mm, ET: 80mm

7 - 40 mm



### LED KONVERTER / LED CONVERTER

<b>24-122204</b>	900mA, not dimmable	1 RIDE 30W
<b>24-15141350</b>	900mA, DALI dimm.	1 RIDE 30W

### LED 47W · 1400mA


634-002030123XX	W2	15°	3840lm
634-002030129XX	W3	15°	4170lm
634-002030124XX	W4	15°	4510lm

634-002030623XX	W2	34° + 15°	3630lm
634-002030629XX	W3	34° + 15°	3950lm
634-002030624XX	W4	34° + 15°	4270lm

634-002030323XX	W2	45°	3840lm
634-002030329XX	W3	45°	4170lm
634-002030324XX	W4	45°	4510lm

37mm x L 876mm, ET: 80mm

7 - 40 mm



### LED KONVERTER / LED CONVERTER

<b>24-1222084</b>	1400mA, not dimmable	1 RIDE 47W
<b>24-123170</b>	1400mA, DALI dimm.	1 RIDE 47W

