



## RIDE R

220-240V AC/DC · CRI >90 · Binning SDCM 3

### SYS 10W (nicht dimmbar/not dimmable)

1:	W2 = 820lm	W3 = 890lm	W4 = 930lm
2:	W2 = 920lm	W3 = 1010lm	W4 = 1050lm
3:	W2 = 780lm	W3 = 850lm	W4 = 880lm

577-01101C023XX0	W2	L: 581mm
577-01101C029XX0	W3	L: 581mm
577-01101C024XX0	W4	L: 581mm

### SYS 15W

1:	W2 = 1230lm	W3 = 1340lm	W4 = 1400lm
2:	W2 = 1390lm	W3 = 1510lm	W4 = 1570lm
3:	W2 = 1170lm	W3 = 1270lm	W4 = 1320lm

577-01102C023XXY	W2	L: 861mm
577-01102C029XXY	W3	L: 861mm
577-01102C024XXY	W4	L: 861mm

LED Lichtprofil aus stranggepresstem Aluminium  
Oberfläche eloxiert, schwarz oder weiß pulverbeschichtet  
LED Konverter im Leuchtenprofil integriert  
Geeignet für den Einbau in Zwischendecken von 7-40mm  
Flache oder vorspringende kubische Abdeckung

LED profile, extruded aluminium  
Anodised surface, white or black powder-coated  
Built-in LED converter in profile  
For false ceiling 7-40mm thickness  
Flat or cubic diffuser

Profilo in alluminio pressofuso a LED  
Finitura anodizzata, verniciatura a polveri bianca o nero  
Converter LED integrato nel profilo  
Idonea per controsoffitti di spessore 7-40mm  
Diffusore piatto o cubico

Profil en Led en aluminium extrudé  
Finition anodisée ou laquée blanc ou noir  
Convertisseur intégré dans le profil  
Pour faux-plafond 7-40mm d'épaisseur  
diffuseur plat ou cubique

W2	= LED 2700K
W3	= LED 3000K
W4	= LED 4000K

### SYS 19W

1:	W2 = 1650lm	W3 = 1790lm	W4 = 1860lm
2:	W2 = 1850lm	W3 = 2020lm	W4 = 2100lm
3:	W2 = 1560lm	W3 = 1700lm	W4 = 1770lm

577-01103C023XXY	W2	L: 1141mm
577-01103C029XXY	W3	L: 1141mm
577-01103C024XXY	W4	L: 1141mm

### SYS 24W

1:	W2 = 2060lm	W3 = 2240lm	W4 = 2330lm
2:	W2 = 2320lm	W3 = 2520lm	W4 = 2620lm
3:	W2 = 1950lm	W3 = 2120lm	W4 = 2210lm

577-01104C023XXY	W2	L: 1421mm
577-01104C029XXY	W3	L: 1421mm
577-01104C024XXY	W4	L: 1421mm

### SYS 48W

1:	W2 = 4130lm	W3 = 4490lm	W4 = 4670lm
2:	W2 = 4640lm	W3 = 5050lm	W4 = 5250lm
3:	W2 = 3910lm	W3 = 4250lm	W4 = 4420lm

577-01105C023XXY	W2	L: 2821mm
577-01105C029XXY	W3	L: 2821mm
577-01105C024XXY	W4	L: 2821mm

### SYS 71W

1:	W2 = 6190lm	W3 = 6730lm	W4 = 7000lm
2:	W2 = 6970lm	W3 = 7570lm	W4 = 7870lm
3:	W2 = 5870lm	W3 = 6380lm	W4 = 6640lm

577-01106C023XXY	W2	L: 4221mm
577-01106C029XXY	W3	L: 4221mm
577-01106C024XXY	W4	L: 4221mm

A++ - A

IP 20

### ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

C = ABDECKUNG/COVER

XX = FARBE/COLOUR

Y = DIMMBAR/DIMMABLE

PMMA opal diffuser flat = 1

W white = 05

S switchable = 0

PMMA opal diffuser cubic = 2

S black = 06

D DALI dimm = d

Microprismatic cover flat = 3

AE aluminium anodized = 08

