



Einbaudownlight aus Aluminium
 Pulverbeschichtet in weiß oder schwarz
 Vakuumbedampfter Alureflektor in 3 Ausstrahlwinkeln
 Strahlerelement 355° drehbar und 30° schwenkbar
 Konverter separat ordern

Recessed downlight in aluminium
 white or black powder-coated
 Vacuum deposited reflector in 3 beam angles
 Spotlight 355° swiveling and 30° tilting
 please order converter separately

downlight in alluminio ad incasso
 verniciato in bianco o nero opaco
 Ottica in alluminio in 3 fasci di emissione
 Proiettore orientabile 355° orizzontale e 30° verticale
 converter da ordinare separatamente

Downlight encastré en aluminium
 Finition laquée blanc ou noir
 Réflecteurs aluminium, 3 faisceaux disponibles
 Projecteur tournant à 355°, pivotant à 30°
 convertisseur à commander séparément

LED 3500K auf Anfrage / on request

Universal-Betoneinbauehäuse: siehe Seite 498-499
 Universal concrete housing: see page 498-499

A++ - A

IP 20

RINE SQUARE R

Binning SDCM 3 exkl. Konverter / excl. converter

Power feed

Order converter not dimm.
 Order converter Dali dimm.

685-0020002WWXX
 685-0020005WWXX
 685-0020008WWXX

| 350mA - 12W | | | 500mA - 17W | | | 700mA - 25W | | | | | |
|-------------|------|------|-------------|------|------|-------------|------|------|----|----|----|
| 24-127530 | | | 24-127532 | | | 24-127534 | | | | | |
| 24-127490 | | | 24-127490 | | | 24-127490 | | | | | |
| lm | W2 | W3 | W4 | lm | W2 | W3 | W4 | lm | W2 | W3 | W4 |
| 1230 | 1280 | 1370 | 1690 | 1760 | 1880 | 2240 | 2330 | 2490 | | | |
| 1230 | 1280 | 1370 | 1690 | 1760 | 1880 | 2240 | 2330 | 2490 | | | |
| 1230 | 1280 | 1370 | 1690 | 1760 | 1880 | 2240 | 2330 | 2490 | | | |

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

WW = LICHTFARBE/LIGHT COLOUR

XX = FARBE/COLOUR

LED 2700K = 43 PREMIUM CRI >90
 LED 3000K = 49 PREMIUM CRI >90
 LED 4000K = 24 CRI >90

white = 05
 black = 06

LED CONVERTER RINE SQUARE

| | | | | |
|-----------|--|----------------------|-----------------|-----------------------|
| 24-127530 | | schaltbar/switchable | for 350mA | L 130 x B 42 x H 30mm |
| 24-127532 | | schaltbar/switchable | for 500mA | L 130 x B 42 x H 30mm |
| 24-127534 | | schaltbar/switchable | for 700mA | L 130 x B 42 x H 30mm |
| 24-127490 | | DALI dimm. | for 350 - 700mA | L 130 x B 42 x H 30mm |

