



LED Strahlschiene aus Aluminiumdruckguss
Feinstrukturlack in weiß, schwarz oder silber matt
Vakuumbedampfter Reflektor in 3 Ausstrahlwinkeln
Strahler 350° drehbar, Leuchtenkopf 90° schwenkbar

Die casting aluminium LED track spotlight
Microstructure painting in white, black or silver matt
Vacuum deposited reflector in 3 beam angles
Spotlight 350° swiveling, head 90° tilting

Proiettore da binario in alluminio pressofuso
Finitura in bianco, nero o grigio opaco
Ottiche in 3 fasci di emissione
Proiettore girevole a 350°, testa orientabile a 90°

Projecteur pour rail en aluminium pressé
Vernissage en blanc, noir ou gris mat
Réflecteur en 3 angles d'émission
Projecteur tournant à 350°, tête pivotant à 90°

W3 = LED 3000K / **PREMIUM CRI > 90**
W4 = LED 4000K / **CRI > 90**

LED 2700 & 3500K auf Anfrage / on request
SONDERLICHTFARBEN auf Anfrage
SPECIAL LIGHT COLOURS on request
WIDE FLOOD 60° auf Anfrage / on request

3-Phasen Schienensystem: Seite 450-455
3-phase track system: page 450 - 455



IP20



reddot award 2015
winner lighting design

SHOPSTAR H TRACK

220-240V AC · Binning SDCM 3 · **PASSIVE COOLING**

SYS 13W

608-001010249XXY 1370lm
608-001010224XXY 1470lm

608-001010549XXY 1370lm
608-001010524XXY 1470lm

608-001010849XXY 1370lm
608-001010824XXY 1470lm

SYS 27W

608-001030249XXY 2500lm
608-001030224XXY 2670lm

608-001030549XXY 2500lm
608-001030524XXY 2670lm

608-001030849XXY 2500lm
608-001030824XXY 2670lm

SYS 40W

608-001060549XXY 3780lm
608-001060524XXY 4040lm

608-001060849XXY 3780lm
608-001060824XXY 4040lm

SYS 19W

608-001020249XXY 1900lm
608-001020224XXY 2030lm

608-001020549XXY 1900lm
608-001020524XXY 2030lm

608-001020849XXY 1900lm
608-001020824XXY 2030lm

SYS 36W

608-001040249XXY 3050lm
608-001040224XXY 3260lm

608-001040549XXY 3050lm
608-001040524XXY 3260lm

608-001040849XXY 3050lm
608-001040824XXY 3260lm

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

XX = FARBE/COLOUR **Y** = DIMMBAR/DIMMABLE

silver matt = 04
 white = 05
 black = 06

switchable = 0
 PULSE DALI dimm = p

