

TECHNICAL DATA SHEET

200CENT ROUND 250LM ADJ SEMI TRIM IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable 0° - 25°

 Ø43 mm - h = 100 mm

Material: Aluminium

Ref N° 200 BL CR



Black Chrome - Nero Cromo
Schwarz Chrom - Zwart Chrom
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

Chiedete una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

Ref N° 200 BL BL



Black Black - Nero Nero
Schwarz Schwarz - Zwart Zwart
Noir Noir - Negro Negro

Ref N° 200 WH BL



White Black - Bianco Nero
Weiß Schwarz - Wit Zwart
Blanc Noir - Bianco Negro

Ref N° 200 BL WH



Black White - Nero Bianco
Schwarz Weiß - Zwart Wit
Noir Blanc - Negro Bianco

Ref N° 200 WH WH



White White - Bianco Bianco
Weiß Weiß - Wit Wit
Blanc Blanc - Bianco Bianco

Ref N° 200 BL GO



Black Gold - Nero Oro
Schwarz Gold - Zwart Goud
Noir Or - Negro Oro

Ref N° 200 WH GO



White Gold - Bianco Oro
Weiß Gold - Wit Goud
Blanc Or - Bianco Oro

Ref N° 200 BL CO



Black Copper - Nero Rame
Schwarz Kupfer - Zwart Koper
Noir Cuivre - Negro Cobre

Ref N° 200 WH CO



White Copper - Bianco Rame
Weiß Kupfer - Wit Koper
Blanc Cuivre - Bianco Cobre

200CENT ROUND ADJ SEMI TRIM 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 533 17 520	REF N° 533 17 920	REF N° 533 17 820	REF N° 533 17 720

3 W - 250LM - 2 step MacAdam - **A+**
Serial wiring -  -  -  - 
Requires remote LED driver - 1050mA
Standard narrowbeam 12° - Optional 8° beam
Ultra low glare (UGR < 13)

INTEGRAL LED DRIVER

REF N° 697 61 015 15W DIM 1-10V Ø40 x 149mm



REF N° 697 31 015 15W DIM DALI Ø40 x 149mm

230V/50Hz -  -  -  - IP20 - 1050mA
fits through the opening of Ø43mm

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W



230V/50Hz -  - current controlled
 -  - IP20 - 1050mA - not dimmable





REMOTE LED DRIVER DIM

REF N° 697 60 025 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 70 050 min 2W max 45W PHASE DIM

230V/50Hz -  - current controlled
 -  - IP20 - 1050mA - dimmable



INSTALLATION KIT

REF N° 680 01 043 standard holesaw Ø 43 mm

BEAM ANGLES

STANDARD (included) beam angle 12°
REF N° 203 20 008 (option) beam angle 8°

TECHNICAL DATA SHEET

200CENT ROUND 500LM ADJ SEMI TRIM IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable 0° - 25°

Ø43 mm - h = 100 mm

Material: Aluminium

Ref N° 200 BL CR



Black Chrome - Nero Cromo
Schwarz Chrom - Zwart Chrom
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

Chiedete una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

Ref N° 200 BL BL



Black Black - Nero Nero
Schwarz Schwarz - Zwart Zwart
Noir Noir - Negro Negro

Ref N° 200 WH BL



White Black - Bianco Nero
Weiß Schwarz - Wit Zwart
Blanc Noir - Bianco Negro

Ref N° 200 BL WH



Black White - Nero Bianco
Schwarz Weiß - Zwart Wit
Noir Blanc - Negro Bianco

Ref N° 200 WH WH



White White - Bianco Bianco
Weiß Weiß - Wit Wit
Blanc Blanc - Bianco Bianco

Ref N° 200 BL GO



Black Gold - Nero Oro
Schwarz Gold - Zwart Goud
Noir Or - Negro Oro

Ref N° 200 WH GO



White Gold - Bianco Oro
Weiß Gold - Wit Goud
Blanc Or - Bianco Oro

Ref N° 200 BL CO



Black Copper - Nero Rame
Schwarz Kupfer - Zwart Koper
Noir Cuivre - Negro Cobre

Ref N° 200 WH CO



White Copper - Bianco Rame
Weiß Kupfer - Wit Koper
Blanc Cuivre - Blanco Cobre

200CENT ROUND ADJ SEMI TRIM 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 533 18 520	REF N° 533 18 920	REF N° 533 18 820	REF N° 533 18 720

5,9 W - 500LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 700mA
Standard Perfectbeam 24° - Optional 44° beam
Ultra low glare (UGR < 13)

INTEGRAL LED DRIVER

REF N° 697 67 015 15W DIM 1-10V Ø40 x 149mm

REF N° 697 37 015 15W DIM DALI Ø40 x 149mm

REF N° 697 77 010 10W PHASE DIM Ø42 x 94mm

230V/50Hz - - - **CE** - IP20 - 700mA
fits through the opening of Ø43mm

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - **CE** - IP20 - 700mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH





REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 77 010 min 2W max 10W PHASE DIM

REF N° 697 77 020 min 11W max 20W PHASE DIM

230V/50Hz - - current controlled
 - **CE** - IP20 - 700mA - dimmable



INSTALLATION KIT

REF N° 680 01 043 standard holesaw Ø 43 mm

BEAM ANGLES

STANDARD (included) beam angle 24°
REF N° 203 20 044 (option) beam angle 44°

TECHNICAL DATA SHEET

200CENT ROUND 750LM ADJ SEMI TRIM IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable 0° - 25°

Ø43 mm - h = 100 mm

Material: Aluminium

Ref N° 200 BL CR



Black Chrome - Nero Cromo
Schwarz Chrom - Zwart Chrom
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

Chiedete una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet-standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

Ref N° 200 BL BL



Black Black - Nero Nero
Schwarz Schwarz - Zwart Zwart
Noir Noir - Negro Negro

Ref N° 200 WH BL



White Black - Bianco Nero
Weiß Schwarz - Wit Zwart
Blanc Noir - Blanco Negro

Ref N° 200 BL WH



Black White - Nero Bianco
Schwarz Weiß - Zwart Wit
Noir Blanc - Negro Bianco

Ref N° 200 WH WH



White White - Bianco Bianco
Weiß Weiß - Wit Wit
Blanc Blanc - Blanco Blanco

Ref N° 200 BL GO



Black Gold - Nero Oro
Schwarz Gold - Zwart Goud
Noir Or - Negro Oro

Ref N° 200 WH GO



White Gold - Bianco Oro
Weiß Gold - Wit Goud
Blanc Or - Blanco Oro

Ref N° 200 BL CO



Black Copper - Nero Rame
Schwarz Kupfer - Zwart Koper
Noir Cuivre - Negro Cobre

Ref N° 200 WH CO



White Copper - Bianco Rame
Weiß Kupfer - Wit Koper
Blanc Cuivre - Blanco Cobre

200CENT ROUND ADJ SEMI TRIM 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 533 19 520	REF N° 533 19 920	REF N° 533 19 820	REF N° 533 19 720

6,2 W - 750LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 250mA
Standard beam angle 36°

INTEGRAL LED DRIVER

REF N° 697 62 015 15W DIM 1-10V Ø40 x 149mm

REF N° 697 32 015 15W DIM DALI Ø40 x 149mm

REF N° 697 70 008 8W PHASE DIM Ø42 x 94mm

230V/50Hz - - - **CE** - IP20 - 250mA
fits through the opening of Ø43mm

REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.2W max. 30W

REF N° 697 00 080 min.27W max. 67W

230V/50Hz - - current controlled
 - **CE** - IP20 - 250mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 30W




1-10V DALI PUSH

REF N° 697 30 070 min 33W max 65W DALI

REF N° 697 60 080 min 27W max 67W 1-10V PUSH

REF N° 697 72 020 min 6W max 12,5W PHASE DIM

230V/50Hz - - current controlled
 - **CE** - IP20 - 250mA - dimmable



INSTALLATION KIT

REF N° 680 01 043 standard holesaw Ø 43 mm

BEAM ANGLES

STANDARD (included) beam angle 36°